

Product data sheet

WRM-24 *



Receiving module for activating automatic doors and window drives with 24 V DC

AREAS OF APPLICATION

- Activation of GEZE automatic doors and window drives via the GEZE wireless program
- Flush-mounted installation



PRODUCT FEATURES

- Encrypted communication via rolling code with up to 74 trillion code combinations
- Simple teach-in via learn button with acoustic feedback
- Up to 85 radio transmitters can be taught
- Integrated DIP switch to select different modes of operation
- Pulse mode, pulse and continuous mode, dead man's mode, or self-locking mode
- Smallest housing dimensions for integrated installation within a flush-mounted socket
- Two outputs for individual connection possibilities

TECHNICAL DATA

Productname	WRM-24 *
Operating current	12.5 mA
Output	2 potential-free relay contacts
IP rating	IP20
Type of installation	Flush-mounted installation
Cable connection type	Screw terminal
Transmission frequency	433.93 Mhz
Service temperature	0 - 50 °C

VARIANTS / ORDER INFO

Designation	Description	Ident-No.	Colour	Dimensions	Output
WRM-24 receiving module *	52 x 47 x 23 mm (W x H x D), for installation in a standard flush-mounted socket / 24 V DC operating voltage, pulsed operation or pulsed and continuous operation	131213	black	52 x 52 x 47 x 23 mm	2 potential-free relay contacts

* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.